

Honda CITY

standard safety equipment





PRIMARY SAFETY

80%

Electronic	Stability	Control	8 N	max.	8
Liectionic	Stability	Control	0 . 0	IIIax.	O

system name Vehicle Stability Assist

Driver Monitoring System **0.0** max. 2

system name —

Tyre Pressure Monitoring 2.0 max. 2

system name Deflation Warning System

warning •

readout •

Blind Spot Monitoring **0.0** max. 2

system name -

input driver side

driver side passenger side

Physical Controls

6.0 max. 6

hazard lights

gear (

climate

music and navigation

turn indicators

windscreen wipers

SECONDARY SAFETY

61%

Rear Seatbelts			4.0 max. 4	
position	outboard	centre	third row	
three-point			0	

Rear Seatbelt Rer	ninders	2.	0 max. 10
position	outboard	centre	third row
visual signal			0
acoustic signal			0
occupant detection	•	•	0
passive activation			\circ

Head Protection Devices			5.0 max	. 6
position	front	rear	third row	
curtain airbag			0	
centre airbag	•	0	0	
Chest Protection [Devices	;	2.0 max	. 3

position front rear thorax airbag

Neck Restra	ints	4.0 max. 4		
position	rear outboard	centre	third row	
$sufficient^1$			0	

Child Read	iness		1.5 r	max. 3
position	rear	rear	front	third
	outboard	centre	passenger	row
ISOFIX		•	•	0
i-Size			•	0
Top Tether			•	0

COMMENTS

A creditable result but the City needs better seatbelt reminders, and unlike LHD versions produced for export, it has no i-Size positions.

primary safety	secondary safety	overall result		
80%	61%			
****	***	***		
Evaluated variant: SV 1.5 i-VTEC MT				
Evaluated on: September 12, 2025				
Protocol: FleetSure v1.0				

¹subjective judgment