

Mahindra **THAR** optional safety equipment





PRIMARY SAFETY

80%

Electronic Stability Control	8.0 max. 8
system name ES	С
Driver Monitoring System	0.0 max. 2
system name —	-
Tyre Pressure Monitoring	2.0 max. 2

system name **Tyretronics** warning

readout

Blind Spot Monitoring **0.0** max. 2

system name input

driver side

passenger side

Physical Controls

6.0 max. 6

hazard lights

gear

climate

music and navigation

turn indicators

windscreen wipers

SECONDARY SAFETY

31%

third row

0

centre

0

Rear Seatbelts			4.0	max.	4
position out	board	centre	third	row	
three-point	•	0	0		
Rear Seatbelt Rem	ninders		0.0 r	nax.	10
position	outboa	rd cen	tre th	ird rov	v
visual signal	•			0	
acoustic signal	•			0	
occupant detection	•			0	
passive activation	•			0	
Head Protection D)evices		0.0	max.	6
position	front	rear	third ro	w	
curtain airbag	•	•	0		
centre airbag	•	0	0		
Chest Protection I	Devices	;	0.0	max.	3
pos	ition f	ront r	ear		
thorax a	irbag	•	•		
Neck Restraints			4.0	max.	4

Child Read	iness		1.5 r	max. 3
position	rear outboard	rear centre	front passenger	third row
ISOFIX		0	•	0
i-Size		0	•	0
Top Tether		0	•	0

position rear outboard

COMMENTS

sufficient1

Results shown here are for a Thar with optional tyre pressure monitoring.

primary	secondary	overall		
safety	safety	result		
80%	31%			
****		****		
Evaluated variant: LX 2.2 mHawk 4x4 AT				
Evaluated on: September 26, 2025				
Protocol: FleetSure v1.0				

¹subjective judgment