

Suzuki EECO standard safety equipment





PRIMARY SAFETY

70%

Electronic Stability Control	8.0 max. 8
system name ESP®	
Driver Monitoring System	0.0 max. 2
system name —	
Tyre Pressure Monitoring	0.0 max. 2
system name —	

Blind	Spot	Monitoring	0.0 max.	2

system name input

warning readout

driver side passenger side

Physical Controls

6.0 max. 6

hazard lights

gear

climate

music and navigation

turn indicators

windscreen wipers

SECONDARY SAFETY

Rear Seatbelts			4.0 max. 4
position out	tboard o	entre t	hird row
three-point	•	0	•
Rear Seatbelt Ren	ninders	6	2.0 max. 10
position	outboard	d centre	e third row
visual signal		0	•
acoustic signal		0	
occupant detection	•	0	•
passive activation	•	0	•
Head Protection [Devices		5.0 max. 6
position	front	rear thi	rd row
curtain airbag			
centre airbag	•	0	0
Chest Protection I	Devices		2.0 max. 3
pos	sition fro	ont rea	r
thorax a		•	
Neck Restraints			0.0 max. 4
position rear o	utboard	centre	third row

Child Read	iness		0.0 r	max. 3
position	rear outboard	rear centre	front passenger	third row
ISOFIX	•	0	Passenger	•
i-Size	•	0	•	
Top Tether		0	•	•

COMMENTS

 $sufficient^1$

The Eeco is evaluated with the optional third row as a worst-case scenario; results for the 5-seat variant can be expected to be similar.

primary	secondary	overall	
safety	safety	result	
70%	43%		

Evaluated variant: Tour V STD AC 6-seat			
Evaluated on: October 2, 2025			
Protocol: FleetSure v1.0			

¹subjective judgment